

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application Serial No. 09/928,172
Filing Date August 9, 2001
Inventor Chris Parfeniuk et al.
Assignee Honeywell International Inc.
Group Art Unit 2823
Examiner W. M. Brewster
Attorney's Docket No. 30-5016-(4015) DIV1
Title: Physical Vapor Deposition Target Constructions

**Assistant Commissioner for Patents
Washington, D.C. 20231**

CERTIFICATE OF FACSIMILE TRANSMISSION UNDER 37 CFR 1.8

I hereby certify that the following papers are being facsimile transmitted to the Patent and Trademark Office at (703) 872-9318 on the date shown below:

FAX RECEIVED

1. Response to Office Action dated December 4, 2002.
2. Version with Markings Showing Changes Made


FEB 28 2003

TECHNOLOGY CENTER 2800

FEE DEFICIENCY

Although it is believed that no fees are due, the Commissioner is hereby authorized to charge any fees under 37 C.F.R. 1.16 and 1.17 which may be required by this paper to Deposit Account No. 23-0925.

Dated: February 28, 2003

By: 
Jennifer Gaines, Legal Assistant
Telephone No. (509) 624-4276

NUMBER OF PAGES IN FACSIMILE: 11

Appl. No. 09/928,172

7/B
3-4-03
Moleish**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Application Serial No. 09/928,172
 Filing Date August 9, 2001
 Inventor..... Chris Parfeniuk et al.
 Assignee..... Honeywell International Inc.
 Group Art Unit..... 2823
 Examiner W. M. Brewster
 Attorney's Docket No. 30-5016-(4015) DIV1
 Title: Physical Vapor Deposition Target Constructions

RESPONSE TO DECEMBER 4, 2002 OFFICE ACTION

To: BOX NON FEE AMENDMENT
 Assistant Commissioner for Patents
 Washington, D.C. 20231

From: David G. Latwesen, Ph.D. (Tel. 509-624-4276; Fax 509-838-3424)
 Wells, St. John, Roberts, Gregory & Matkin P.S.
 601 W. First Avenue, Suite 1300
 Spokane, WA 99201-3828

FAX RECEIVED**AMENDMENTS**

FEB 28 2003

TECHNOLOGY CENTER 2800

In the Specification

Replace the paragraph beginning on line 13 of page 6 with the following text,

--A method encompassed by the present invention is described by a flow diagram in Fig. 2. At an initial step (labeled 30 in Fig. 2) work hardening is done to a target material. If, for example, the target material comprises aluminum, work hardening can be introduced by compressing the aluminum from an initial thickness to a second thickness. Such compression is illustrated in Fig. 3, wherein a target 50 is illustrated before and after